

IDS

1120 ULTRA GLOSS ULTRA HIGH WEAR FLOOR FINISH

Vinyl
Vinyl Asbestos
Asphalt
Linoleum
Rubber



Concrete
Flagstone
Brick
Sealed Wood
Quarry Tile

Requires no authorization for use in U.S.D.A. offices and non-processing areas.

Product Description

A fast drying ultra durable floor finish with exceptional buffability. Tests on high traffic floor produce wear levels dramatically superior to conventional floor polishes on the market today. This unique product is ready for traffic immediately after application without burnishing. After weeks of wear it will snap back to its original beauty with the aid of a spray buff or mop-on restorer.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and Federal regulations.

Test:

Type:	Highly crosslinked acrylic
Non-volatile Solids:	20.0 ± 0.5%
Color:	Milky white
Odor:	Mild
pH:	8.5 - 9.0
Dry/Recoat Time:	45 minutes min.
Slip Resistance:	.56 - .60 (ASTM-D2047-82)
Gloss:	90+ specular
Leveling:	Excellent
Buffability:	Spray buff or restorer
Removability:	With instant type strippers
Detergent Resistance:	Excellent
Waterspot Resistance:	Excellent
Heel Mark Resistance:	Excellent
VOC Content:	0.35 lbs./gal.
Storage/Stability:	2 years
Freeze / Thaw Stability:	Keep from freezing
Weight Per Gallon:	8.62 lbs./gal.
Coverage:	2000-2500 ft ² per gal.

Limit:

Directions For Use

PREPARATION: If stripping is necessary, use an IDS quality stripper and follow directions accordingly. If floor is in good condition and stripping is not necessary; sweep up excess dirt and dust and then clean with a good quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow to dry completely.

FINISHING: Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Two or three coats are desired initially, depending on the condition of the floor and gloss desired.

MAINTENANCE: The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

FOR INDUSTRIAL AND INSTITUTIONAL USE

IDS

Supply King