

# IDS

## 1140 GLOSS COAT ACRYLIC FLOOR FINISH

Vinyl  
Vinyl Asbestos  
Asphalt  
Linoleum  
Rubber



Concrete  
Flagstone  
Brick  
Sealed Wood  
Quarry Tile

Requires no authorization for use in U.S.D.A. offices and non-processing areas.

### Product Description

A metal cross-linked, acrylic floor finish with high initial gloss and durability with exceptional responsiveness to spray buffing. Excellent for schools and institutions. A true workhorse in any maintenance program.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and Federal regulations.

### Test:

<b>Type:</b>	Modified acrylic
<b>Non-volatile Solids:</b>	18.0 ± 0.5%
<b>Color:</b>	Milky white
<b>Odor:</b>	Mild
<b>pH:</b>	8.5 - 9.0
<b>Dry/Recoat Time:</b>	30 minutes min.
<b>Slip Resistance:</b>	.56 - .60 (ASTM-D2047-82)
<b>Gloss:</b>	90+ specular
<b>Leveling:</b>	Excellent
<b>Buffability:</b>	Spray buff or restorer
<b>Removability:</b>	With conventional strippers
<b>Detergent Resistance:</b>	Excellent
<b>Waterspot Resistance:</b>	Excellent
<b>Heel Mark Resistance:</b>	Excellent
<b>VOC Content:</b>	0.31 lbs./gal.
<b>Storage/Stability:</b>	2 years
<b>Freeze / Thaw Stability:</b>	Keep from freezing
<b>Weight Per Gallon:</b>	8.56 lbs./gal.
<b>Coverage:</b>	2000-2500 ft <sup>2</sup> per gal.

### Limit:

### Directions For Use

**PREPARATION:** If stripping is necessary, use an IDS quality product and follow directions accordingly. If floor is in good condition and stripping is not necessary, sweep up excess dirt and dust and then clean with a good quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow to dry completely.

**FINISHING:** If floor was stripped, use a good acrylic sealer to further prepare the floor for finishing. Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Two or three coats are desired initially, depending on the condition of the floor and gloss desired.

**MAINTENANCE:** The floor may be maintained using a quality floor cleaner and damp mopping regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

FOR INDUSTRIAL AND INSTITUTIONAL USE

# IDS

## Supply King