

# IDS

## 1310 DYNAMITE HEAVY DUTY NO RINSE SPEED STRIPPER

Vinyl Asbestos  
Linoleum  
\*Asphalt Tile  
\*Rubber  
Terrazzo



Vinyl  
Concrete  
Sealed Wood  
Flagstone  
Ceramic Tile

### Product Description

The most effective floor finish emulsifier ever developed. Will solubilize aged and built-up finishes almost instantly. May be used as a no-scrub stripper or with a conventional floor machine and pad depending on the concentration of the product and the condition of the floor.

### Test:

<b>Active Ingredients:</b>	50.0 ± 0.5%
<b>Color:</b>	Clear
<b>Odor:</b>	Sassafras
<b>pH (concentrate):</b>	13.0 - 13.5
<b>Viscosity:</b>	Water thin
<b>Foam:</b>	Low
<b>Abrasives:</b>	None
<b>Phosphate Content:</b>	None
<b>Solubility:</b>	Complete with water
<b>Emulsification:</b>	Excellent
<b>Detergency:</b>	Excellent
<b>Rinsability:</b>	Excellent
<b>Flash Point:</b>	168°F (TCC)
<b>Biodegradability:</b>	Completely
<b>Storage/Stability:</b>	2 years
<b>Weight Per Gallon:</b>	8.27 lbs. per gallon
<b>Freeze / Thaw Stability:</b>	Keep from freezing

### Limit:

### Directions For Use

The desired concentration will depend on the build-up and age of the polish film. As a starting point dilute with cold water as follows:

**FOR AVERAGE BUILD-UPS** - Dilute 1 to 3 with cold water.

**FOR MODERATE BUILD-UPS** - Dilute 1 to 2 with cold water.

**FOR HEAVY AGED BUILD-UPS** - Dilute 1 to 1 with cold water.

**FOR USE WITH A FLOOR MACHINE** - Dilute 1 to 8-16 parts cold water.

Mop a generous solution onto the floor to be stripped. Allow solution to stand about 5 minutes keeping the floor wet at all times. If mop stripping - agitate with the mop. If using an automatic scrubber or rotary floor machine, no mop agitation is required. Pick-up the solution with a wet vacuum, automatic scrubber or clean mop. Allow floor to dry thoroughly prior to applying any sealer or finish. If desired, a rinsing step can be added.

NOTE: Asphalt tile and rubber flooring could be affected by stripping solutions in high concentrations. Always test floor before proceeding.

\* test first

# IDS

**Supply King**